

Serial No. 09/708,817  
June 30, 2003  
Reply to the Office Action dated December 31, 2002  
Page 11 of 18

#### REMARKS/ARGUMENTS

Claims 1-26 are pending in this application. By this Amendment, Applicant AMENDS claim 1-4, 8, 9, 11, 14-17, 21, 22, and 24 and the Specification.

Applicant has made minor clarifying amendments to claims 1-4, 8, 9, 11, 14-17, 21, 22, and 24.

---

Applicant has enclosed herewith a substitute Specification and a marked-up Specification showing the changes that were made. Applicant has made only minor grammatical corrections to the specification. No new matter has been added. Accordingly, Applicant respectfully requests that the originally filed Specification be replaced with the substitute Specification filed herewith.

The drawings were objected to for failing to designate Figs. 1-5B as --Prior Art--. Applicant has amended Figs. 1-5B in the accompanying replacement drawing sheets to properly be designated as --Prior Art--. Accordingly, Applicant respectfully requests reconsideration and withdrawal of the objection to the drawings.

Claims 1-9, 12-22, 25, and 26 were rejected under 35 U.S.C. §102(e) as being anticipated by Masuda (U.S. 5,982,272). Claims 10, 11, 23, and 24 were rejected under 35 U.S.C. §103(a) as being unpatentable over Masuda in view of Applicant's admitted Prior Art (AAPA) **Figs. 2 and 4**. Applicant respectfully traverses the rejection of claims 1-26.

Claim 1 has been amended to recite:

“A variable resistor comprising:  
a case;  
a rotor rotatably mounted in said case, said rotor being arranged to be rotationally operated from outside of the case;  
a substrate provided in said case, said substrate having a collector electrode disposed at an approximately central portion of the surface of the substrate and having an arcuate resistor disposed on the surface of the substrate around said collector electrode so as to be substantially concentric therewith;  
a slider mounted on said rotor so as to be rotatable together with said rotor;

Serial No. 09/708,817

June 30, 2003

Reply to the Office Action dated December 31, 2002

Page 12 of 18

said slider including:

a base portion with a rear surface being supported by said rotor;

an annular arm portion having a bent up portion bent along a bending line corresponding to a diameter of the annular arm portion and arranged to make sliding contact with said arcuate resistor of said substrate;

~~a substantially I-shaped arm portion located inside of the~~  
annular arm portion, extending in a direction that is substantially perpendicular to the bending line, and arranged to make contact with said collector electrode; and

**a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion.” (emphasis added)**

Applicant's claim 1 recites the features of “a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion.” Applicant's claim 14 recites similar features as claim 1. With the improved features of claims 1 and 14, Applicant has been able to provide a variable resistor with a low profile and a stable contact between the slider and the substrate (see, for example, the last full paragraph on page 4 and the first paragraph on page 7 of the Specification).

Applicant agrees with the Examiner that Masuda et al. shows a variable resistor. However, Masuda clearly fails to teach or suggest the feature of “a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion” as recited in Applicant's claims 1 and 14.

Masuda clearly teaches that the annular arm portion **42** is connected to the body portion **41** via **one folded back portion disposed at one end** of the body portion and that the substantially I-shaped portion **43** is connected to the body portion **41** via **another folded back portions disposed at the opposite end** of the body portion **41**, **NOT** that the annular arm portion **and** the substantially I-shaped portion are connected to the body portion by **a folded back portion** at **one end** of the base portion as recited in Applicant's claims 1 and 14.

Since the present claimed invention requires that the annular arm portion and the

Serial No. 09/708,817

June 30, 2003

Reply to the Office Action dated December 31, 2002

Page 13 of 18

substantially I-shaped are connected to the same end portion of the body portion via the folded back portion, and Masuda clearly teaches that the annular arm portion and the substantially I-shaped portion are connected to two different ends of the main body portion via two different folded back portions, Masuda clearly fails to teach or suggest each and every feature recited in the present claimed invention, including "a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion."

Accordingly, Applicant respectfully requests reconsideration and withdrawal of the rejection of claims 1 and 14 under 35 U.S.C. §102(e) as being anticipated by Masuda.

Further, Masuda teaches that "[t]he arm lengths (the distance from a folded-bent end to the contact point portion) of the first arm **42** and the second arm **43** of the slider **4** are substantially equivalent to each to each other, and accordingly, the spring performance of both arms **42** and **43** are set substantially equal to each other" in order to reduce "an inclination of a rotor load" (see lines 5-7 of column 2 and lines 10-14 of column 7). That is, the first **42** and second **43** arms must be on opposite sides in order that they have substantially equal arm lengths. Masuda clearly teaches away from the feature of "a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion" as recited in Applicant's claims 1 and 14. Because Masuda teaches away from Applicant's claimed invention, Masuda cannot be relied upon in an obviousness rejection. The Examiner is reminded that it is an error to find obviousness where references diverge and teach away from the invention at hand. W.L. Gore & Assoc. v. Garlock Inc., 721 F.2d 1540, 1550, 220 USPQ 303, 311 (Fed. Cir. 1983).

The Examiner has relied upon AAPA to cure various deficiencies of Masuda. However, AAPA clearly fails to teach or suggest the feature of "a folded back portion coupling one end of the base portion with the annular arm portion and the substantially I-shaped arm portion" as recited in Applicant's claims 1 and 14.

Serial No. 09/708,817  
June 30, 2003  
Reply to the Office Action dated December 31, 2002  
Page 14 of 18

Accordingly, Applicant respectfully submits that Masuda and AAPA, applied alone or in combination, fail to teach or suggest the unique combination and arrangement of elements recited in claims 1 and 14 of the present application. Claims 2-13 depend upon claim 1, and are therefore allowable for at least the reasons that claim 1 is allowable. Claims 15-26 depend upon claim 14, and are therefore allowable for at least the reasons that claim 14 is allowable.

In view of the foregoing amendments and remarks, Applicant respectfully submits that this application is in condition for allowance. Favorable consideration and prompt allowance are solicited.

To the extent necessary, Applicants petition the Commissioner for a THREE-month extension of time, extending to June 30, 2003, the period for response to the Office Action dated December 31, 2002.

The Commissioner is authorized to charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 50-1353.

Respectfully submitted,

Date: June 30, 2003

  
Attorneys for Applicant

Joseph R. Keating  
Registration No. 37,368

Christopher A. Bennett  
Registration No. 46,710

**KEATING & BENNETT LLP**  
10400 Eaton Place, Suite 312  
Fairfax, VA 22030  
Telephone: (703) 385-5200  
Facsimile: (703) 385-5080



- 1 -

Marked-up Version

Attorney Docket No. 36856.394

VARIABLE RESISTOR

---

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a variable resistor used in ~~industrial equipment devices~~ such as a hearing aid, a measuring instrument, communications equipment, a sensor, or other such electronic apparatus, and in particular, the present invention relates to a miniaturized variable resistor.

2. Description of the Related Art

In recent years, reduction in the size and the weight of electronic equipment has been ~~required~~ desired, and the reduction in the size and the weight of the circuit components provided within such electronic equipment ~~are also required to be small-sized components~~ has also been desired. ~~For a variable resistor which is used in a circuit, a~~ An ultra-miniature variable resistor having a diameter or side length of about 2 mm has been used as a circuit component. A variable resistor requires a slider which is a spring component. However, the miniaturization of the

slider makes it difficult to achieve good electrical contact and sliding characteristics.

~~In~~ Figs. 1 and 2 show a conventional ultra-miniature variable resistor having a structure in which a shaft 2, a rotor 3, a slider 4, and a substrate 5 are provided in a case 1, and which ~~is~~ are sealed by filling a sealing resin 6 such as epoxy resin in the bottom opening of the case 1, ~~is shown~~. Here, ~~Lead~~ terminals 71, 72, and 73 are fixed on the substrate 5. The lead terminals are electrically connected to both sides of an arcuate resistor 51 and a collector electrode 52, respectively.

As shown in Fig. 3, the slider 4 is defined by a thin metallic plate having a annular arm portion 41 making sliding contact with the arcuate resistor 51 of the substrate 5, and an I-shaped arm portion 42 arranged to contact the collector electrode 52 of the substrate 5. The annular arm portion 41 is bent up at the portion corresponding to the diameter, and the I-shaped arm portion 42 extends in a direction that is substantially perpendicular to the bent-up line of the annular arm portion 41, and is located inside of the annular arm portion 41. In the left side view of Fig. 3, the solid line designates the slider state under a load, and the two-dot chain line designates the slider state without a load. In the slider 4, a pair of through holes 44 for fitting ~~to~~ the protrusions 31 (see Fig. 4) of the rotor 3 are provided at bilaterally symmetrical

positions around the I-shaped arm portion 42. The slider 4 is mounted on the rotor 3 so as to be rotatable together with the rotor 3, by fitting the protrusions into the through holes 44, and then crushing the protrusions 31 by weld-caulking.

As shown in Figs. 5A and 5B, ~~in the variable resistor~~  
~~having the above-described features,~~ when the substrate is mounted in the variable resistor, both of the annular arm portion 41 and the I-shaped arm portion 42 are subjected to a load. As a result, a moment M in the backward-tilting direction of the slider 4 occurs ~~with respect to the slider 4 around about the bending-up line 43~~ root of the bent up portion of the annular arm portion 41, as a fulcrum (see Fig. 5B). The distance between the the protrusions 31 and the bending-up line 43 define the fulcrum about which the moment M acts. Once a backward-tilting of the slider 4 occurs, a problem arises that the contact between the resistor 51 and the annular arm portion 41, and the contact between the collector electrode 52 and the I-shaped arm portion 42 become unstable, resulting in a reduction in the reliability of the variable resistor.

In order to prevent the slider 4 from backwardly tilting, the protrusions 31 of the rotor 3 are weld-caulked. However, ~~since because~~ the two protrusions 31 ~~to be weld-caulked are~~ arranged in the vicinity of the bending-up line 43 ~~of the annular arm portion 41,~~ the distance between the protrusions 31 and the

bending-up line 43 defining the fulcrum is small, ~~so that~~.  
Because the distance defining the fulcrum is small, the backward-tilting of the slider 4 cannot be effectively prevented. Furthermore, in the case of very small components, protrusions 31 having a sufficient size cannot be formed on the rotor 3, and ~~also the welding-weld-caulkingwork~~ of the protrusions 31 is very difficult. For example, when the diameter of the slider 4 is 1.5 mm, the diameter of the protrusions needs to be about 0.2 mm to effectively prevent the backward-tilting of the slider 4. The process of welding such ~~a~~ small protrusions 31 is thus very difficult, and a desired fixing strength cannot be reliably achieved even though welding is executed.

#### SUMMARY OF THE INVENTION

In order to overcome the problems described above, the preferred embodiments of the present invention provide a variable resistor arranged to effectively and reliably prevent a slider from backwardly tilting toward a rotor, ~~and~~ thereby maintaining a stable contact between the slider and a substrate.

According to one of the preferred embodiments of the present invention, a variable resistor includes a case, a rotor rotatably accommodated in the case, the rotor being rotationally operated from the outside of the case, a substrate located in the case, the substrate having a collector electrode at an



approximate central portion of the surface thereof, and having an arcuate resistor disposed ~~outside of~~ around the collector electrode so as to be substantially concentric therewith, a slider mounted on the rotor so as to be rotatable together with the rotor. ~~‡~~ The slider having an annular arm portion arranged to achieve sliding contact with the arcuate resistor on the substrate, ~~and having~~ a substantially I-shaped arm portion arranged to contact the collector electrode, and a base portion that is integral with the slider. ~~‡~~ The base portion being coupled at one end thereof with the annular arm portion and the substantially I-shaped arm portion by a folded-back structure, ~~and~~. The base portion extending extends up to the vicinity of the position corresponding to the tip portion of the annular arm portion. ~~‡~~ The rear surface of the base portion ~~being is~~ supported by the rotor. In this variable resistor, the annular arm portion is bent up at the portion corresponding to the diameter or at the portion in the vicinity ~~thereof~~ of the diameter. The substantially I-shaped arm portion extends in a direction that is substantially perpendicular to the bent-up line of the annular arm portion, and is located inside ~~of~~ the annular arm portion.

The annular arm portion of the slider rotates and makes sliding contact with the arcuate resistor of the substrate ~~around~~. ~~‡~~ The substantially I-shaped arm portion ~~making~~ makes contact with

the collector electrode of the substrate, ~~as a fulcrum. In such an operational state in which~~ When both of the annular arm portion and the substantially I-shaped arm portion are under a load, a moment about the bent-up line of the annular arm portion and in the backward-tilting direction acts on the slider ~~around the root of the bent up portion of the annular arm portion, as a fulcrum.~~

---

In the slider in accordance with a preferred embodiment of the present invention, ~~however,~~ a base portion is integral with the slider, ~~and.~~ The base portion is coupled with the annular arm portion and the substantially I-shaped arm portion by ~~the a~~ a folded-back structure, ~~and.~~ The base portion extends up to the vicinity of the position corresponding to the tip portion of the annular arm portion. With this configuration, the base portion supports the moment in the backward-tilting direction, ~~and can~~ surely prevents the slider from backwardly tilting. This stabilizes the contact between the resistor and the annular arm portion, ~~and that~~ the contact between the collector electrode and the substantially I-shaped arm portion, which leads to an improvement in the reliability of the variable resistor.

Preferably, the annular arm portion, the substantially I-shaped arm portion, and the base portion are coupled such that the base portion is folded back, and the annular arm portion, the substantially I-shaped arm portion, and the base portion are closely contacted by the folded-back structure. Thereby, the

height dimension of the slider can be made smaller than the ~~usual~~  
~~U-shaped folded-back~~ structures of the prior art. This allows  
variable resistors ~~in~~ of the preferred embodiments of the present  
invention to ~~be more low-profile~~ have lower profiles.

It is preferable that the substantially I-shaped arm  
portion is raised without folding the substantially I-shaped arm  
portion. This is accomplished by ~~folding~~ bending a portion of  
the folded-back portion ~~between the annular arm portion and the~~  
~~base portion~~ in the direction opposite to the bending-up  
direction of the annular arm portion. In the slider having a  
conventional structure, ~~since~~ because the substantially I-shaped  
arm portion is ~~folded~~ bent and raised, work-hardening occurs in  
the ~~folded~~ bent portion under the influence of bending work<sub>7</sub>.  
The work-hardening of the bent portion ~~with the results that in~~  
the elastic region in the substantially I-shaped arm portion  
becoming smaller<sub>7</sub>. ~~That is,~~ the effective spring length  $L_1$   
~~thereof~~ of the substantially I-shaped arm portion (see Fig. 5A)  
becomes smaller. This ~~creates a~~ causes the problem that the  
contact pressure between the substantially I-shaped arm portion  
and the collector electrode becomes greater than is needed. On  
the other hand, in the above-described construction in accordance  
with a preferred embodiment of the present invention, ~~since the~~  
work-hardening due to bending work is prevented because the  
substantially I-shaped arm portion is substantially linear, and

the raising of the root portion of the substantially I-shaped arm portion by folding is not done, ~~work-hardening due to bending work does not occur,~~ and the stress with respect to the load disperses throughout the substantially I-shaped arm portion. This allows results in the substantially I-shaped arm portion  
having a wider elastic region to be available. That is, it is possible to make the effective spring length longer, and to set the contact pressure between the substantially I-shaped arm portion and the collector electrode to an appropriate value.

Preferably, a pair of through holes for fitting ~~to the~~ protrusions of the rotor are provided ~~on the opposite surfaces of~~ in the annular arm portion and the base portion in the vicinity of the folded-back structure portion, and substantially at bilaterally symmetrical positions around the substantially I-shaped arm portion. Specifically, the through holes are preferably arranged at common positions relative to the annular arm portion and the base portion, ~~and.~~ The insertion of the protrusions of the rotor into the through holes of the slider prevents the slider from slipping with respect to the rotor, when the rotor is rotated. ~~In this case, since~~ Because the slider is prevented from backwardly tilting, there is no need to fix the protrusions by weld-caulking. Also, ~~since the load applied on the protrusions is small, even such thin protrusions do not cause any problem~~ because the load applied on the protrusions is small.

The above-described variable resistor in accordance with a preferred embodiment of the present invention may be applied to hearing aids. In hearing aids, variable resistors are used for sensibility adjustment or other adjustment. In accordance with the desire to miniaturization ~~miniaturize of~~ hearing aids, ~~miniature size variable resistors have been required. Use of a variable resistor of miniature size and having stable characteristics allows the reliability of a hearing aid to be greatly improved.~~

In the present invention, the method for attaching the slider and rotor is not limited to the conventional method in which the protrusions are weld-caulked. This is because the slider would not slip with respect to the rotor ~~by virtue~~ because of the spring forces of the arm portions ~~if only the rotation of the base portion with respect to the rotor is stopped.~~

The above and other characteristics, elements, features, and advantages of the present invention will be apparent from the following detailed description of preferred embodiments of the invention in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view showing a conventional variable resistor.

Fig. 2 is an exploded perspective view showing the variable

resistor shown in Fig. 1.

Fig. 3 illustrates a left-side view, a front view, and a cross-sectional view taken along the line A-A in the front view, each showing the slider included in the variable resistor in Fig. 1.

---

Fig. 4 is a perspective view showing the slider and rotor used in the variable resistor shown in Fig. 1, as viewed from the rear side.

Figs. 5A and 5B are partially sectional views illustrating the variable resistor before and after the substrate is built in the variable resistor shown in Fig. 1, respectively.

Fig. 6 is a cross-sectional view illustrating an example of a variable resistor in accordance with a preferred embodiment of the present invention.

Fig. 7 is an exploded perspective view illustrating the variable resistor shown in Fig. 6.

Fig. 8 illustrates a left side view, a front view, a cross-sectional view taken along the line B-B in the front view, and a rear elevation each showing the slider used in the variable resistor in Fig. 6.

Fig. 9 is a front development view illustrating the slider shown in Fig. 8.

Fig. 10 is a perspective view illustrating the slider and rotor used in the variable resistor shown in Fig. 6, as viewed

from the rear side.

Figs. 11A and 11B are partially sectional views illustrating the variable resistor before and after the substrate is built in the variable resistor shown in Fig. 6, respectively.

---

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Figs. 6 through 11 illustrate an example of a variable resistor in accordance with a preferred embodiment of the present invention. This example of a variable resistor is used for, for example, a hearing aid.

~~Since~~ Because this variable resistor has the same structure as the variable resistor shown in Figs. 1 through 5, except for the slider 8, the same elements and parts as shown in Figs. 1 through 5 are identified by the same reference numerals in Figs. 6 through 11 to avoid repetitive description.

A case 1 is molded in one piece so as to have a substantially cylindrical shape using a heat-resistant thermoplastic resin or thermosetting resin, in order to resist the heating generated by soldering and to allow a stable operation in a high-temperature atmosphere.

A substantially circular opening 11 is provided in the top surface of the case 1, and a stopper portion 12 is arranged to protrude from the inner peripheral surface thereof. A stopper portion 21 for a shaft 2 is inserted into the opening 11, and the

rotational angle of the shaft 2 is regulated by abutting the stopper portion 21 of the shaft against the stopper portion 12 of the case. The shaft 2 is also preferably made of the same material as the case 1, but may alternatively be formed of a metal. On the top end surface of the shaft 2, a tool engaging groove 22 is arranged to extend in the axial diametric direction. A thin shaft portion 23 is arranged to protrude from the bottom end surface of the shaft 2. A substantially cylindrical internal space 13 accommodating the rotor 3, the slider 8, and the substrate 5 is provided in the lower portion of the case 1. The substrate 5 is fitted to the lower-end opening portion 14 of the case 1. The substrate 5 is prevented from slipping off the lower-end opening portion 14 by inwardly thermal-caulking the end portion of this opening portion. A sealing resin is filled into the recess defined by the lower-end opening portion 14 and the substrate 5 and is arranged to seal the recess.

The rotor 3 is also molded in one piece into a disk shape using the same material as the case 1, and a hole 32 to be fitted into the shaft portion 23 of the shaft 2 is provided at the approximate center of the rotor. The shaft 2 and the rotor 3 are integrated, by inserting the shaft portion 23 of the shaft 2 into the hole 32, and thermal-caulking the tip thereof. As-Instead of using of the method in which the tip of the shaft portion 23 is thermal-caulked, ~~coupling member for the shaft 2 and rotor 3, for~~



~~example~~, a claw portion, for preventing the shaft portion 23 from slipping off, may be provided at the tip of the shaft portion 23\_ as a coupling member of the shaft 2 and rotor 3, ~~in place of the method in which the tip of the shaft portion 23 is thermal-~~ ~~caulked~~. Two protrusions 31 are provided on the bottom surface of the rotor 3 for preventing the slipping rotation of the slider 8 with respect to the rotor 3.

The substrate 5 defines a disk to be fitted into the lower-end opening 14 of the case 1, and is molded ~~integrally~~ using the same material as the case 1. A through hole is provided at the approximate center of the surface of the substrate 5, ~~and~~ ~~the~~ upper end of the lead terminal 73 is fitted into the approximately central through hole and is exposed on the surface of the substrate 5. The upper end of the lead terminal 73 ~~constituting~~ constitutes a collector electrode 52. An arcuate resistor 51 ~~around the collector electrode 52~~ is provided on the surface of the substrate 5 around the collector electrode 52. Through holes are also provided in both ends of ~~this~~ the resistor 51, ~~and~~ ~~the~~ The lead terminals 71 and 72 are inserted into these through holes and are connected to both ends of the resistor 51. ~~Meanwhile,~~ Figs. 6 and 7 show an example of a lead terminal type variable resistor in which the lead terminals 71 ~~through~~ 73 are inserted into the through holes in the substrate 5, but the type of variable resistor is not ~~particularly~~ limited to this type.

The variable resistor in accordance with various preferred embodiments of the present invention may be constructed as a surface-mount type, omitting the lead terminals 71-73.

The slider 8 is preferably made of a conductive thin metallic plate formed of a copper alloy, stainless steel, a  
precious metal based alloy, or other suitable material having  
good spring properties.~~7 and~~ The slider 8 is subjected to surface processing using a precious metal or other suitable material, as appropriate. As shown in Fig. 8, in the slider 8, an annular arm portion 81, ~~an~~ substantially I-shaped arm portion 82, and a base portion 83 are stamped out from one metallic plate~~7~~ ~~which are connected together~~. The annular arm portion 81, substantially I-shaped arm portion 82, and base portion 83 are folded back in a closely contacted state at the coupling portion 84 ~~defining a boundary~~. The annular arm portion 81 is bent up along the bending-up line 85 in ~~the~~ a diametric direction, and a sliding contact 81a~~,~~ for making sliding contact with the arcuate resistor 51 of the substrate 5, is arranged to protrude from the tip portion of the annular arm portion 81. The substantially I-shaped arm portion 82 extends in a direction that is substantially perpendicular to the bending-up line 85 of the annular arm portion 81~~7~~. ~~and~~ The substantially I-shaped arm  
portion 82 is a linear arm located inside the annular arm portion 81. A contact member 82a arranged to contact the collector

electrode 52 is arranged to protrude from the tip of the substantially I-shaped arm portion 82.

The base portion 83 is constructed as a disk having substantially the same diameter as the annular arm portion 81. The base portion 83 extends up to the vicinity of the position corresponding to the tip portion of the annular arm portion 81 where the sliding contact member 81a is provided. The rear surface of the base portion 83 is supported ~~on~~ by the surface of the rotor 3. A fold-back portion 86, near the coupling portion 84 where the base portion and the annular and I-shaped arm portions are folded and closely contacted, is folded in the direction opposite to the bending-up direction of the annular arm portion 81. ~~and~~ ~~the~~ The substantially I-shaped arm portion 82 is not folded, but is raised. That is, the substantially I-shaped arm portion 82 extends linearly from the folded-back point at the coupling portion 84. Corresponding to this fold-back portion 86, an inclined surface 33 (see Fig. 10) is defined on the bottom surface of the rotor 3. A pair of through holes 87 and 88 for fitting ~~to~~ the protrusions 31 of the rotor 3 are provided on the closely contacted surfaces of the annular arm portion 81 and the base portion 83, ~~at the area except the bending-up line 85~~. The through holes 87 and 88 are arranged substantially at bilaterally symmetrical positions around the substantially I-shaped arm portion 82. After the protrusions 31 have been inserted into the

through holes 87 and 88, they are not required to be weld-caulked.

As described above, ~~since~~because the substantially I-shaped arm portion 82 extends linearly from the folded-back point at the coupling portion 84, the elastic region of the substantially I-shaped arm portion 82 becomes longer as shown in Fig. 11. ~~That is, the effective spring length  $L_2$  thereof of~~the substantially I-shaped arm portion 82 becomes larger. This allows the contact pressure between the substantially I-shaped arm portion 82 and the collector electrode 52 to be set to an appropriate value.

Here, the effective spring length of the annular arm portion 81 is the distance from the bending-up line 85 to the sliding contact 81a.

In this preferred embodiment of the present invention, ~~since~~because the effective spring length of the annular arm portion 81 and that of the substantially I-shaped arm portion 82 of the slider 8 are substantially the same, the spring elasticity of the two arm portions 81 and 82 are also ~~preferably~~ substantially the same.

As shown in Fig. 11, when the substrate 5 is assembled into the case 1, ~~since~~because both of the annular arm portion 81 and the substantially I-shaped arm portion 82 are subjected to a load, a moment in the backward-tilting direction occurs with respect to the slider 8 ~~around~~about the bending-up line 85 of the annular

arm portion 81, ~~as a fulcrum~~ (see Fig. 8B). However, ~~since~~ because the slider 8 is integral with the base portion 83, and the rear surface of ~~this~~ the base portion 83 is supported by the rotor 3, it is possible to stably support the slider 8 with respect to the moment  $M_7$  and to reliably prevent the slider 8 from backwardly tilting. This arrangement stabilizes the contact between the resistor 51 and the annular arm portion 81, ~~and that~~ the contact between the collector electrode 52 and the substantially I-shaped arm portion 82, which greatly improves reliability.

The protrusions 31, which are fitted in the through holes 87 and 88, have no need to prevent the slider 8 from backwardly tilting, but have only to prevent the slipping rotation of the slider 8 with respect to the rotor 3. The protrusions 31, therefore, are not required to be weld-caulked. Also, ~~since~~ because the protrusions 31 are subjected to only a small load, they can prevent a damage of the slider even if the protrusions 31 are small.

The present invention is not limited to the above-described preferred embodiments. The shape of the base portion 83 is not limited to a disk shape. Alternatively, any shape, such as an annular shape, a cross shape, or other shapes may be used. Corresponding to this, an engaging portion for stopping the rotation of the base portion 83 may also be provided on the

bottom surface of the rotor 3. Any shape may be used which meets the conditions that the base portion 83 is supported by the rotor 3 over a wide region in the longitudinal direction of the annular arm portion 81, and ~~which~~ that can support a moment M in the backward-tilting direction applied to the slider 8, ~~may be used~~.

---

Also, although the annular arm portion 81, the substantially I-shaped arm portion 82, and the base portion 83 are folded back in a closely contacted state, they may be folded back without being closely contacted.

Furthermore, the outer shape of the case 1 is not limited to a substantially cylindrical shape, but it may be a square cylindrical shape or other shape. In this case, it is preferable that the outer shape of the substrate 5 be not a disk-like shape, but have a square-plate shape.

In the present invention, the shape of the annular arm portion of the slider is not limited to an annular shape in the strict sense. The term "annular shape" used herein is a concept including similar shapes. It is possible that the shape of the annular arm portion of the slider constitutes a closed loop. Also, the shape of the substantially I-shaped arm portion is not limited to an I-shaped configuration, in the strict sense, but has only to be substantially linear.

~~As is evident from the above description, in accordance with preferred embodiments of the present invention, in the state~~

~~in which~~ When the annular arm portion and the substantially I-shaped arm portion are in pressure contact with the substrate, a moment in the backward-tilting direction acts on the slider around ~~the root of the bent up portion of the annular arm portion,~~ as a fulcrum, ~~but in the slider, since~~ Because a ~~the~~ base portion ~~which is coupled with the annular arm portion and the substantially I-shaped arm portion by a folded-back structure is integral with the slider, and~~ because the base portion extends up to the vicinity of the position corresponding to the tip portion of the annular arm portion, ~~as well as~~ and because the rear surface of the base portion is supported by the rotor, the base portion supports the moment in the backward-tilting direction, and ~~can surely~~ prevents the slider from backwardly tilting. This arrangement stabilizes the contact between the resistor and the annular arm portion, ~~and that~~ the contact between the collector electrode and the substantially I-shaped arm portion, which leads to greatly improved reliability.

Moreover, in accordance with various preferred embodiments of the present invention, ~~since~~ because the slider does not necessarily need to be fixed with respect to the rotor by weld-caulking, unlike the conventional art, and only the rotation of the slider with respect to the rotor needs to be stopped by any engaging structure, it is possible to simplify the assembling work.

While the present invention has been described with reference to the preferred embodiments thereof, many modifications may be applied in the light of the above teachings. It is therefore to be understood that within the scope of the appended claims, the invention may be practiced otherwise than as specifically described.

---



### Marked-up Version

#### ABSTRACT OF THE DISCLOSURE

A variable resistor is constructed to prevent a slider from backwardly tilting toward a rotor, and to thereby maintain stable contact between the slider and a substrate. In the variable resistor, a rotor and a slider are provided in a case, and a substrate having a collector electrode and an arcuate resistor on the surface thereof is mounted in the lower end portion of the case. In the slider, an integral unit includes an annular arm portion arranged to achieve sliding contact with the arcuate resistor on the substrate, a substantially I-shaped arm portion arranged to contact the collector electrode, and a base portion coupled with the annular arm portion and the substantially I-shaped arm portion defined by a folded-back structure, and the base portion extends up to the vicinity of the position corresponding to the tip portion of the annular arm portion. The rear surface of the base portion is supported by the rotor such that the slider is prevented from backwardly tilting.